

Basic flow A Series



AIR CURTAIN (220V50Hz)



0.02m	—————	11.3 m/s
0.5m	—————	9.9 m/s
1.0m	—————	6.8 m/s
1.5m	—————	5.5 m/s
2.0m	—————	4.7 m/s
2.5m	—————	3.8 m/s
3.0m	—————	3.2 m/s
3.5m	—————	2.9 m/s
4.0m	—————	2.7 m/s

- Compact metal casing finished in structural epoxy-polyester painting;
- Standard white RAL9016. Other colors or stainless steel casing are optional.
- Optimized tangential fan wheel provides stable & even air flow at low noise level.
- Control: remote control or touch switch are standard; thermostat controller, automatic magnetic door switch, limit switch are optional.
- Application places: commercial shops cafeteria, bakery, shop, restaurants, hospital.
- Installation height: 2.5m – 3m.

Door magnetic switch are optional.



TECHNICAL PARAMETERS

Model	Dimension (mm)	Frequency (Hz)	Voltage (V~)	Motor Power (W)	Air velocity(m/s)		Air volume (m³/h)	Noise(dB)		Net weight (kg)
					HI	LO		HI	LO	
A-90	900×210×175	50/60	220-240	160	11	9	1630	57	53	12.5
A-100	1000×210×175	50/60	220-240	185	11	9	1910	58	54	13.5
A-120	1200×210×175	50/60	220-240	220	11	9	2500	58	54	15.7
A-150	1500×210×175	50/60	220-240	260	11	9	3580	59	55	18
A-180	1800×210×175	50/60	220-240	320	11	9	3900	60	57	20
A-200	2000×210×175	50/60	220-240	350	11	9	4280	61	57	22