

Basic flow B+ Series

Bigger, Stronger, Better.



AIR CURTAIN (220V50Hz)



0.02m	11.1 m/s
0.5m	9.6 m/s
1.0m	6.7 m/s
1.5m	5.3 m/s
2.0m	4.6 m/s
2.5m	3.8 m/s
3.0m	3.2 m/s
3.5m	2.6 m/s
4.0m	2.5 m/s

- Compact metal casing finished in structural epoxy-polyester painting;
- Standard color: white RAL9016 and black. Other colors are optional.
- Bigger tangential fan wheel provides stable & even air flow at low noise level.
- Control: remote control or touch switch are standard; automatic magnetic door switch are optional.
- Application places: commercial shops cafeteria, bakery, shop, restaurants, hospital.
- Installation height: 2.5m – 3.5m.



Technical Specifications

Model	Dimension (mm)	Frequency (Hz)	Voltage (V~)	Motor Power (W)	Air velocity(m/s)		Air volume (m³/h)	Noise(dB)	
					HI	LO		HI	LO
BP-90	900×225×190	50	220-240	150	12	10	1780	55	54
BP-100	1000×225×190	50	220-240	155	12	10	1980	56	55
BP-120	1200×225×190	50	220-240	170	12	10	2370	58	54
BP-150	1500×225×190	50	220-240	180	12	10	2970	59	55
BP-180	1800×225×190	50	220-240	240	12	10	3560	60	57
BP-200	2000×225×190	50	220-240	300	12	10	3850	61	59